


## vMEyeV2 (android version) instructions

1、Open the mobile monitoring software, log in according to the serial number.



The diagram illustrates the navigation process. At the top, a blue rectangular bar represents a header. Below it, a white rectangular area contains two grey buttons: 'Address pattern' and 'Series number pattern'. The 'Series number pattern' button is highlighted with a red rectangular border. Below this, another blue rectangular bar represents a footer. A large red arrow points downwards from the 'Series number pattern' button to the 'Serial setting' screen.

The 'Serial setting' screen is a mobile application interface with a black header bar containing a 'Back' button and the title 'Serial setting'. Below the header, there are four input fields: 'Serial number' (containing '003e0b00b42c'), 'Server' (containing 'www.dvrcenter.com'), 'User name' (containing 'admin'), and 'Password' (empty). At the bottom of the screen, there are three buttons: 'Edit', 'Delete', and 'Cancel'.

Server: Enter [www.dvrcenter.com](http://www.dvrcenter.com). User name is admin, no password, Serial number is the same with the device. Check it through main menu→system information→version information, or via IE configuration→system setting→net setting, as follows:

Device config

Setting -> System -> Network

Net Card: Wire Netcard ☐ DHCP Enable

IP Address: 10 . 2 . 59 . 59

Subnet Mask: 255 . 255 . 0 . 0

Gateway: 10 . 2 . 0 . 1

Use DNS server address below-----

Primary DNS: 192 . 168 . 1 . 1

Secondary DNS: 8 . 8 . 8 . 8

Media Port: 34567 HTTP Port: 80

MAC: 00: c1: 75: 08: 22: 93

☐ High Speed Download

Transfer Policy: Quality Preferred

Refresh OK Cancel

2、After setting, log in sequenced number to carry out mobile monitoring, as follows:





Put the phone horizontally to get the maximized preview.